

● Parameter

SMQT®

Interface	Supports EIA / TIA RS-232 and RS-485.
Connectors	Supports USB and DB9 (RS-485) connectors.
Protocol	Supports RS-232 and RS-485 protocols.
Transfer Rate	57.6 Kbps (1200 baud rate, 230 characters per second)
Power Consumption	5 W (USB 1200 baud rate (RS-485))

● Introduction

SMQT®

This is a USB to RS485 converter. It converts USB to RS485.

It contains a USB to RS485 converter chip (ASIC).

RS-485 7-wire twisted pair cable, 12V ~ 12V + 5V

98% compatibility with Windows 2000 / XP

Supports USB v5.0

Supports USB V1.1 and USB CDC V1.1

USB to RS485 converter

Supports USB to RS485 converter chip (ASIC)

Supports RS-485 7-wire twisted pair cable

57.6 Kbps (1200 baud rate, 230 characters per second) 1200 baud rate

Supports EIA / TIA RS-485 protocol

Supports RS-485 7-wire twisted pair cable

Supports RS-485 7-wire twisted pair cable (RS-485 7-wire twisted pair cable 485 32-wire twisted pair cable)

● Dimension Picture

SMQT®



● Installations

SMQT®

Switch Power supply



Door release button



Standalone Access controller



PC

Converter(USB to RS 485)

EA-02



● Features



1. 32-bit (ASIC) 32Kbit USB 2.0/1.1 雙埠通訊
 2. 支援 USB1.1 / 2.0 埠通訊
 3. 460800 位元速率
 4. 128 位元 TX / RX 512 位元
 5. 支援 Win95 / 98 / 98SE / ME / 2000 / XP / NT3.5
 6. 支援 USB 通訊
 7. 支援 RS485 通訊

● Packing list



數量	100 / 包裝
產品尺寸 (mm)	53L * 40W * 36.5H (mm)

● Office



● Exhibitions



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....