

LED backlight door release button

- Stainless steel and aluminum panel
- Stainless steel button with LED light
- Blue/red/green led light color optional
- 100000~500000 times mechanical test
- Suitable for access control system



Parameter



| | |
|------|---|
| 品名 | LED 背光 / 不锈钢面板 门磁按钮 |
| 型号 | EA-27 |
| 尺寸 | EA-27A: 91 × 28 × 20 (mm) EA-27B / D: 86 × 86 × 20 (mm) EA-27C: 86 × 50 × 20 (mm) |
| 材质 | 不锈钢 面板 铝合金 按钮 不锈钢 面板 按钮 |
| 额定电压 | 3A 36V 直流 电压 |
| 额定电流 | NO / NC / COM |
| 使用寿命 | 500000 ~ 1000000 次机械测试 |
| 工作电压 | 0 ~ 36V |
| 工作温度 | -20 °C ~ 55 °C |
| 相对湿度 | 20% ~ 95% |
| 重量 | EA-27A: 0.072kg EA-27B: 0.106kg EA-27C: 0.132kg EA-27D: 0.194kg |

In-kind shooting





• *Feature*

SMQT



EA-27A



EA-27B



EA-27C



EA-27D



THE ONE

Strong stability

PC rubber seal lock core,
resistance to heat shock,
500, 000 times mechanical test
qualified, suitable for all
Access control system



THE SECOND

Superior Design

Simple and beautiful appearance,
stainless steel wire drawing
panel.



THE THIRD

OEM

LED backlight's color red/blue
green optional, print logo or
other service

Application

SMQT

Switch Power supply



Door release button EA-27



Converter (RS232 to RS485)



Standalone controller



PC

Packaging & shipping

SMQT

| | |
|---------------------|--------------------------------|
| □□□□□□ □□□□□□ □□□□□ | |
| □□□□□ □□□ | EA-27 LED □□□□□ □□ □□□□□ |
| □□□□□□ | 100 □□□□□□ □□ □□□□ □□□□□□ □□□□ |
| □□□□□□ □□□□□ □□□ | 47 * 37 * 29 (□□) |
| □□□ | 8 ~ 20KG |



Office show

SMQT®



Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

