

RFID IC / ID قارئ لوحة التحكم في الوصول إلى باب واحد مع تردد IP66 مقاوم للماء اختياري



EA-82K المعلمة الرئيسية

الوصف:	قارئ بطاقة RFID IC / ID مع تردد IP66 مقاوم للماء
النموذج:	EA-82K
الجهد الكهربائي:	9 ~ 15V
القدرة:	<1W
الحجم:	96× 96 × 22 (مم)
عدد البطاقات:	10000
نوع البطاقة RFID:	IC (13.56MHZ) (نشط)
مسافة القراءة:	3 ~ 5CM
ميزات:	قارئ بطاقة RFID IC / ID مع تردد IP66 مقاوم للماء
تطبيقات:	قارئ بطاقة RFID IC / ID مع تردد IP66 مقاوم للماء
المواد:	ABS مقاوم للماء + مقاوم للحريق
الوزن:	270G

色調指定:	色調指定 netural 色調指定 色調指定 37 色調指定 1
色調指定 色調指定	-35 °C ~ 65 °C
色調指定 色調指定:	20 ~ 80
色調指定:	1 色調指定 色調指定
OEM:	色調指定 OEM




Main parameter

Power supply	DC 9-15V
Power consumption	< 1 W
Card type	13.56 MHz/125 KHz (Optional)
Read range	5-8cm
Capacity of records	10000
Number of users	10000
Communication port	RS485
Transmit Rate	9600 bps (N, 8, 1)
LED Tips	Card flashing/keypad/doorbell
Data storage	4M bits FLASH Memory
Certification	Card fishing/ Card flashing+password/ UID+password/ Public password
Clock	Yes
Reading tips	Beeper/LED
Dimension	96× 96×22(mm)
Material	PC+ABS
Environment	-30℃to+65℃

Appearance





Wiring diagram



Wire port specification		
NO	Function	Description
1	RS485+	Data +
2	RS485-	Data -
3	12V+	DC Power 12V
4	GND	GND
5	OUT-NC	Door relay NC interface
6	OUT-COM.	Door relay COM interface
7	OUT-NO.	Door relay NO interface
8*	IN 1	Input 1, door release button input
9*	IN 2	Input 2, door magnet signal input
10*	IN 3	Input 3, user-defined
11	OC OUT	Build-in doorbell signal output
12*	OUT 2	OC signal, duress output
13*	OUT 3	OC signal, anti-tamper output
14	GND	GND
15	OUT 12V+	Power output, can be connected to WG reader power +
16	GND	Power output, can be connected to WG reader power GND
17	DATA 0	WG Data 0 input, connect reader Data 0
18	DATA 1	WG Data 1 input, connect reader Data 1
19	GND	GND
20	OC1-OUT	Unregistered card output, OC signal output for 3s after card flashing to open the door, can connect Green LED end of WG reader.
21	OC2-OUT	Unregistered card output, OC signal output for 3s after card flashing but not to open the door, can connect Red LED end of WG reader.
22	OC3-OUT	Unregistered card output, OC signal output for 3 times after card flashing to open the door, each interval time is 100ms, can connect Beeper end of WG reader.
23	NULL	N/A
24	ANTI-TAMPER-IN	Anti-tamper signal input, connect anti-tamper output signal of WG reader

Installation



کیف حول خیار آخر؟

SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技

