

# Wired metal magnetic contact sensor

NO/NC Code mode optional

50±10(mm) gap distance

Max voltage≤100V DC,Max current≤500mA

Suitable for metal door or window

Material:mode A is Alloy-zn

mode B is ABS

Silver color

Weight:mode A 158g,mode B 62g



## Parameter

SMQT

产品型号	EB-139
产品尺寸	106 × 16 × 16 (mm)
触点类型	NO / NC (可选)
安装间隙	50 ± 10 (mm)
最大电压	≤100V DC
最大电流	≤500mA
最大功率	≤10W
材料	合金 / ABS
重量	A: 158g / B: 62g

## In-kind shooting

SMQT



• *Feature*

**SMQT**



**EB-139A**



**EA-139B**

*Wired magnetic contact sensor*

*NO/NC code mode optional*

*50±10(mm) gap distance*

*MAX voltage:≤100V DC,MAX current≤500mA*

*Material: mode A:Alloy-zn, mode B:ABS*

*Suitable for metal door or window*

*Color:grey silver*

*Weight: mode A:158g mode B:62g*

*Welcome OEM and 2 years quality warranty*

● *Packaging & shipping*

**SMQT**

	□□□□□□□□ □□□□□□ □□□□□□
□□□□□□ □□□□	□□□□□□□□ □□□□□□□□□□ □□□□□□□□ □□□□□□ □□□□□□ EB-139
□□□□□□	200pcs □□□□□□ □□□□
□□□□□□ □□□□□□ □□□□	37 * 30 * 20 (□□)
□□□□	26 ~ 37kg



WE LOGISTICS



## • Office show

SMQT



## • Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....