

SMQT OLED Screen Access Control Card Reader EA-93DK

- Unique appearance design.
- OLED screen.
- IC (13.56Mhz) card type
- WG26/34 communication(optional)
- Short-circuit protection lightning protection
- Plug type connection easy to intallation



● Parameter

SMQT®

| | |
|----------------------|--|
| | □□□□□ |
| □□□ | □□□□ OLED IC (13.56MHZ) □□□□□□ □□ □□□□□□ □□□□ □□□□ |
| □□□□□ | EA-93DK |
| □□□ | 96 × 96 × 22 (□□□) |
| □□□□□□ □□□□□□□□ □□□□ | 12V ± 3VDC |
| □□□□□□ □□□□□□ | □□□□□□□ & It1 □W |
| □□□□□□□ □□□ | 13.56MHZ IC |
| □□□□□□□□ □□□ | 60MM |
| □□□□ □□□□□□ | 150M |
| □□□□□□□□ □□□□□ | WG26 / WG34 |
| □□□ □□□□ | 1bit / □□□□ |
| □□□□□□□□ □□□□ □□□□□ | 4 □□□bit / 8 □□□bit |
| □□□□□ | □□□□□□□□ □□□□ / □□□□□ |
| □□□□□□ □□ | □□□□□□□□□□ |
| □ □□□□ | □□□□□□□□ □□□□ □□□□□□ □□□□□ □□□□ |
| □□□□□□ □□□□□ □□□□ | -30 °C ~ 65 °C |
| □□□□□□ □□□□□ | 0.2KG |

● Introduction

SMQT®



EA-93DK

OLED screen IC(13.56Mhz) Wiegand card reader

IC(13.56Mz,h)Card type

Wiegand 26/34communication(optioanl)

OLED Dispaly Screen

Laser carving and wer-resisting keyboard

High safety,short-circuit and lightning protection,tamper device

Plug type connection, easy to install

2 years warranty, Welcome OEM

• *In-kind shooting*

SMQT



• Installation

SMQT®



• Packaging & shipping

SMQT®

| | |
|----------------------|--|
| 1. 产品规格表 产品规格表 产品规格表 | |
| 产品规格表 | 产品规格表 OLED 产品规格表 IC (13.56MHZ) 产品规格表 产品规格表 产品规格表 EA-93DK |
| 产品规格表 | 36 产品规格表 产品规格表 产品规格表 产品规格表 |
| 产品规格表 产品规格表 产品规格表 | 45 * 32 * 32 (mm) |
| 产品规格表 | 9KG |



● *Office show*

SMQT®



● *Exhibition*

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....