



## • *Parameter*

**SMQT**

□□	
□□□□	2□□□□□□□□□□□□□□
□□	ABT-20 ABT-40 ABT-60 ABT-80 ABT-100
□□	20□40□60□80□ □□□ 60□120□180□240□ 300□□□□□
□□□□	13.8-24vDC 11-18vAC
□□□□	40-65mA
□□□□	50-700m / SC
□□□□	-20°C□50°C□
□□□□	NO / NC
□□□□	NC
□□□□	180°□±90°□
□□□□	±10°
□□	PC□□

## • *Introduction*

**SMQT**



• *Feature*

**SMQT**



Sealed integration structure is able to work in the harsh environment

Automatically regulate to confront with fog or inclement weather

Sensitivity (AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built-in integrated optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes, low-power digital

---

## • *Installation*

**SMQT**



• *Packaging & shipping*

**SMQT**

	□□□□
□□□□	ABT 2□□□□□□□□□□□□□□
□□	□□20□
□□□□	51 * 48 * 38□□□□
□□	21□□



## • Office show

SMQT®



## • Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....