

LED backlight door release button

- Stainless steel and aluminum panel
- Stainless steel button with LED light
- Blue/red/green led light color optional
- 100000~500000 times mechanical test
- Suitable for access control system

SMQT®



• Parameter

SMQT®

Especificación	
Nombre del producto	Interruptor de la puerta del contraluz del LED / botón abierto
Modelo	EA-27
Dimensión	EA - 27A: 91 x 28 x 20 (mm) EA-27B / D: 86 x 86 x 20 (mm) EA - 27C: 86 x 50 x 20 (mm)
Estándar Estructura	Panel de acero inoxidable, botón de acero
Valoración actual	3A 36V DC Max
Salida de contacto	NO / NC / COM
Prueba mecánica	Prueba 500000 ~ 100.000 veces
Opcional Accesorios	ocultando la caja
Rango adecuado	Botón de puerta abierta
Color	Gris plateado
Uso	Control de acceso sistema
Humedad relativa	0 ~ 95%
Ambiente temprature	-20 °C -55 °C
Material del panel	Acero inoxidable o Panel de aluminio, dibujo de alambre terminado
Peso neto	EA - 27A: 0,072 kg EA - 27B: 0,106 kg EA - 27C: 0.132 kg EA - 27D: 0.194 kg

• In-kind shooting

SMQT®



• *Feature*

SMQT



EA-27A



EA-27B



EA-27C



EA-27D



THE ONE

Strong stability

PC rubber seal lock core,
resistance to heat shock,
500, 000 times mechanical test
qualified, suitable for all
Access control system



THE SECOND

Superior Design

Simple and beautiful appearance,
stainless steel wire drawing
panel.



THE THIRD

OEM

LED backlight's color red/blue
green optional, print logo or
other service

• Application

SMQT®

Switch Power supply



Door release
button EA-27



Converter
(RS232 to RS485)



Standalone
controller



PC

• Packaging & shipping

SMQT®

Lista de envases

Nombre del producto	EA-27 Botón de liberación de la puerta del LED
Cantidad	100 unidades por caja
Tamaño del cartón	47 * 37 * 29 (cm)
Peso	8 ~ 20kg



Office show

SMQT®



Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

