

| Especificación | |
|---------------------------|---|
| Nombre del producto | Luz estroboscópica alarmante con cable |
| Modelo | EB-169 |
| Tensión nominal | DC12V DC24V |
| Frecuencia intermitente | 90 latidos / min |
| Tensión de funcionamiento | 9-15VDC 20-28VDC |
| Camino ligero | Luces LED brillan |
| Corriente de trabajo | 12V≤80mA / 24V≤100mA |
| Luces de encendido | 2W 5W |
| Vida | ≥1000 horas (operación continua de potencia estándar) |
| Talla | 72 * 42 (mm) |



Combination of fixed base plate

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

Strobe indicator light

LED lights, flash frequency up to 90 times a minute.







Strobe Alarming light

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

LED guide plate

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



● Packing list

SMOT

| Lista de embalaje | |
|--------------------------|----------------------------|
| Nombre del producto | Alarma cableada Sluz trobe |
| Cantidad | 100 piezas / caja |
| Tamaño del cartón | 38.3 * 35.3 * 30.3 (cm) |
| Peso | 12 kg |



● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair