Wired embedded magnetic contact

NC/NO mode optional

35±5(mm) gap distance

Max voltage≤100VDC, Max current≤500mA

Suitable for metal door or window

White/Brown color optional

24g weight

SMQT

• Parameter

SMQT

Parámetro	
Nombre del producto	Sensor de contacto magnético emulado
Modelo	EB-136
Dimensión	Φ19 × 25 (mm)
Modo de código	NO / NC (opcional)
Brecha	35 ± 5 (mm)
Tensión máxima	≤ 100V DC
corriente maxima	≤500mA
Max rating	≤ 10W
Color	Marrón / Blanco (opcional)
Estar hecho para	Puerta o ventana metálica
Material	Carcasa anti-incendio ABS
Temperatura de trabajo	-10 ℃ ~ 50 ℃
Peso neto	24 g

• In-kind shooting

SMQT

•*Feature*

EB-136

Dimension:	Φ19*25(mm)
Material:	ABS
Max Gap:	≤40mm
Install way:	Drill hole install
Wire:	22# wire 40cm
Power:	0.5A 10W

Fire-proofing materials

Adopt ABS flame retardant material, fire retardant safer,connecting with 22 # wire, total length of 30 cm. Suitable for metal doors and cabinet door, etc.

Waterproof seal

Using imported PC glue sealing, close the magnet and wiring, waterproof, and durable leakage, using more safe and more comfortable

Strong magnetism

Magnetic strength, which can be installed directly drilling, stable performance.

•Packaging & shipping

SMQT

Lista de envases	
Nombre del producto	Sensor de contacto magnético emulado EB-136
Cantidad	600 piezas por caja
Tamaño del cartón	38 * 30 * 30 (cm)
Peso	16kg

•Office show

SMQT

•*Exhibition*

SMQT