



## • *Parameter*

**SMQT**

<b>detalye</b>	
Pangalan ng Produkto	2 beams outdoor infrared perimeter detector
modelo	ABT-20 ABT-40 ABT-60 ABT-80 ABT-100
distansya	20m 40m 60m 80m 100m (Panlabas) 60m 120m 180m 240m 300m (sa looban)
operating boltahe	13.8-24vDC 11-18vAC
operating kasalukuyang	40-65mA
induction speed	50-700m / sc
enviroment temp	-20 ° C-50 ° C
Alarm output	NO / NC
Anti-demolition output	NC
adjustment Level	180 ° (± 90 °)
vertical adjustment	± 10 °
materyal	PC dagta

## • *Introduction*

**SMQT**



• *Feature*

**SMQT**



Sealed integration structure is able to work in the harsh environment

Automatically regulate to confront with fog or inclement weather

Sensitivity (AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built-in integrated optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes, low-power digital

---

## • *Installation*

**SMQT**



## • *Packaging & shipping*

**SMQT**

<b>listahan packaging</b>	
Pangalan ng Produkto	ABT 2 beams outdoor infrared perimeter detector
Dami	20 mga PC ng bawat karton
carton laki	51 * 48 * 38 (cm)
timbang	21kg



• *Office show*

SMQT®



• *Exhibition*

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....