

● Parameter

SMQT®

Dimensions	106 * 16 * 16 (mm)
connection	Normally open / normally closed
operating distance	50 ± 10 (mm)
Maximum pressure	≤100VDC
load current	≤500mA
working Power	≤10W
housing Material	A zinc alloy B ABS
shape color	silver
scope	Iron door or window
product weight	158g / 62g

● Introduction

SMQT®

Magnetic switch consists of two parts and the magnet switch, switch sections connected by a reed switch by lead, stereotypes package is made; the magnet portion of the corresponding magnetic field strength of the magnet is wrapped in plastic or metal housing. When two or separately close to a certain distance, thereby causing breaking switch sensing changes in body position. Waterproof seal, high adsorption, responsive, beautiful appearance. magnetic contact is also referred to as door sensor and door switch. It works with security alarm systems and door access control is systems. We VIP alibaba.com.

● Dimesion Picture

SMQT®



● Installations


SMQT®



● Features

SMOT

Powerful Fireproof Materials

Magnetic contact is made of safe industrial ABS fireproof materials. 22# 400mm cable is easy to connect other accessories. 





High Sensitivity

High quality magnetic works perfect reed switch. So that magnetic contact work sensitively and effectively.

Total Waterproof Design

Magnetic contact is sealed by PC, so that it is waterproof and has a long work life. Without surface leakage. More safe.



● Packing list

SMQT

model	EB-139A	EB-139b
QTY	200pairs / CTN	200pairs / CTN
Size Package	37.5L * 29.5W * 20H (cm)	37.5L * 29.5W * 20H (cm)
Total weight	36.62kg	29.13kg

● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

