

Especificação	
Nome do Produto	Luz estroboscópica com fio com alarme
Modelo	EB-169
Tensão nominal	DC12V DC24V
Frequência intermitente	90 batimentos / min
Tensão operacional	9-15VDC 20-28VDC
Maneira clara	Luzes LED brilham
Corrente de trabalho	12V≤80mA / 24V≤100mA
Luzes de energia	2W 5W
Vida	≥1000 horas (operação contínua de energia padrão)
Tamanho	72 * 42 (mm)



Combination of fixed base plate

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

Strobe indicator light

LED lights, flash frequency up to 90 times a minute.



● Dimesion Picture

SMQT



● Features

SMQT



Strobe Alarming light

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

LED guide plate

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



● Packing list

SMOT

Lista de embalagem	
Nome do Produto	Alarme com fio Sluz estroboscópica
Qtde	100 pçs / caixa
Tamanho da caixa	38,3 * 35,3 * 30,3 (cm)
Peso	12Kg



● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



.....



2015 Shenzhen Fair