Parameter

SMQT

Габаритные размеры	65 * 30 * 17 (мм)
Рабочее напряжение	3,7 В / 200 мАч
Время зарядки	> 12 часов
Время работы аккумулятора при полной нагрузке	≤ 1 год
разрыв	40 ± 5 мм
Радиочастота	315 МГц / 433 МГц / 868 МГц
Расстояние передачи	≤100 м (под открытым небом)

Introduction

SMQT

Огнестойкий материал корпуса, безопасность и стабильность.
Стабильная, стабильная производительность, зеленый.
Гибкая пропускная способность, варианты стабильности частоты.
Беспроводной замок датчика контакта двери с частотой тревоги 433 МГц или 868 МГц, подходит для использования в дверях или окнах.

Dimesion Picture

SMQT

Installations

SMQT

Wireless Magnetic Contact Sensor

The unique door/window magnetic contact with the emergency button in security industry

. make sure more safety for user;

· Induce the door or window open or close and gap in 10mm, the wireless transmission up to 80 meter.

Stable, stable performance, green.

Flexible transmission capacity, frequency stability options.

Features

SMQT

Multifunctional, the new model, patented design.

Tradition, stability, durability

Imported touch reed switch

Fire-retardant casing material, security and stability.

Comes with emergency button, an accessory, a variety of uses.

Built-in battery, used or release anytime.

Smart power-saving built-in battery design,the sensor also can work at home even tougth power cut out, comes with high-energy battery, sustainable use of uninterruptible power supply

Reed , A special magnetic switch

Imports Reed touch than the general mechanical switch of simple structure, small size, high speed, long working life, and strong anti-shock load, high operating reliability.

Packing list

SMQT

Кол-во	200 / коробка
Спецификации упаковки	40 * 30 * 20 (см)
Вес упаковки	10Kg

Office

SMQT

Exhibitions

SMQT

2011 Brazil Fair
2012 Shenyang Fair
2013 Jinan Fair
2013 Shenzhen Fair
共赢
.....
2012 Shenyang Fair
2013 Shenyang Fair
2013 Shenzhen Fair
2015 Shenzhen Fair