

Wired infrared 2 beams perimeter detector



no intruding
no across



• Parameter

SMQT®

□□□□□□□□□□□□□□	0□□□□□□□□□□ Beam utdoor □□□□□□
□□□□□□□□□□□□	ABT
□□□□□□□□□□□□□□□□□□□□	13.8 ~ 24VDC 11 ~ 28VAC
□□□□□□□□□□□□□□□□□□□□	40-65mA
□□□□□□□□□□□□□□□□□□□□	50 ~ 700m / □□□□□□
□□□□□□□□□□□□□□□□□□□□	□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□	-20 °C ~ + 50 °C
□□□□□□□□□□□□□□	NO / NC
□□□□□□□□□□□□	180 °± 90 °
□□□□ Vertical	± 10 °
□□	□□□□
□□□□□	□□□□□□□□□□

• Introduction

SMQT®

PRODUCT PICTURE



PRODUCT FEATURE



Sealed integration structure is able to work in the harsh environment

Automatically regulate to confront with fog or inclement weather

Sensitivity (AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built-in integrate optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes, low-power digital

• *Packaging & shipping*

SMQT®



● *Office show*

SMQT®



● *Exhibition*

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....