

• Parameter

SMQT

□□□□□□□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□	ABH
□□□□□□□□□□□□	□□□□□: 150m 300m 450m 600m 750m □□□□□□□□: 50m 100m 150m 200m 250m (□□□□□□□□□□□□)
□□□□□□□□□□□□□□□□□□	13.8 ~ 24VDC 11 ~ 28VAC
□□□□□□□□□□□□□□□□□□	40-65mA
□□□□□□□□□□□□□□□□□□	50 ~ 700m / □□□□□□
□□□□□□□□□□□□□□□□□□□□	□□□□□□□□□□□□
Environment	-20 °C ~ + 50 °C
□□□□□□□□□□□□□□□□□□	NO / NC
□□□□□□□□□□□□	180 °± 90 °
□□□□□□□□□□□□	± 10 °
□□	□□□□
□□□□□	□□□□□□□□□□

• Introduction

SMQT

PRODUCT PICTURE



PRODUCT FEATURE



Sealed integration structure is able to work in the harsh environment

Automatically regulate to confront with fog or inclement weather

Sensitivity (AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built-in integrate optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes, low-power digital

1. Sealed

2. Confronted

(AGC circuit)

3. Easily

4. Built



● Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....