

Wired magnetic contact sensor

NC/NO code mode optional

20±5(mm) gap distance

MAX voltage≤100V DC,MAX current≤500mA

Suitable for wooden door or window

Fireproof ABS material shell

White/Brown color optional

8g weight



• Parameter



产品名称	磁性接触传感器
型号	EB-135
规格	Φ10× 18.5 (mm)
触点类型	NO / NC (可选)
间隙	20 ± 5 (mm)
额定电压	≤100VDC
额定电流	≤500mA
额定功率	≤10W
材质	ABS / 塑料 (可选)
颜色	白色 / 棕色 (可选)
应用	适用于木质门/窗 ABS 材质
工作温度	-10 °C ~ 50 °C
重量	8g

• In-kind shooting





• *Feature*

SMQT



Door Magnetic Contact safe door happy life




(Notice: need match the home alarm system to



Sash window

In window close status, door magnetic host and magnetic stripe respectively embedded in the two Windows, do not to leave a gap between, open the window after the success of alarming, Then to fixed.




Notice:
Gap < 2cm




Sliding window

In window close status, door magnetic host and magnetic stripe respectively embedded in the two Windows, do not to leave a gap between, open the window after the success of alarming, Then to fixed.

2 Color optional



White



Brown

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....