



Single door standalone controller keypad

Imported PC material shell 100000 user capacity

- ▶ IC card(13.56Mhz)
- ▶ IP66 grade waterproof
- ▶ Free software, RS485 communication format
- ▶ Can connect external WG(26/34) card reader

● Parameter

SMQT®

型号	EA-92 (100000用户容量)
供电电压	DC12 ± DC3V
功耗	& lt; 1W
识别频率	125KHz ID
厚度	60mm
识别距离	150m
接口	WG26 / 34
识别精度	1bit / MS
尺寸	96L ***** 96W 22H (mm)
工作温度	0℃
存储温度	-30 °C ~ + 65 °C

● Introduction

SMQT®



2 Color optional
 OLED Screen
 Door bell button
 Wear-resisting number key
 Imported PC material shell

RFID frequency. This RFID
 frequency. This RFID

(),
 WG26 / 34
 (IP66)
 /

• *Installation*



• Packaging & shipping

SMQT®



• Office show

SMQT®



• Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....