Parameter

SMQT

số sản phẩm	EA-22A	EA-22B
Cơ cấu tiêu chuẩn	tấm nhôm, nút kim loại	tấm nhôm, nút kim loại
hiệu suất điện	Hiện tại 3A36VDC độ bền tối đa	Hiện tại 3A36VDC độ bền tối đa
kiểm tra độ bền	500.000 lần thử nghiệm lão hóa	500.000 lần thử nghiệm lão hóa
Đối với Loại	khung rỗng áp dụng và hộp điện chìm	khung rỗng áp dụng và hộp điện chìm
Nhiệt độ	-10 ~ + 55 ℃	-10 ~ + 55 ℃
độ ẩm áp dụng	0-95% (độ ẩm tương đối)	0-95% (độ ẩm tương đối)
bảng điều chỉnh chế biến	tấm nhôm phun cát	tấm nhôm phun cát

Introduction

SMQT

Cửa nút khóa phát hành với kim loại nguyên liệu và thép đẩy nút

thoát không gỉ cho hệ thống kiểm soát truy cập.

•Feature

SMQT

EA-22A

EA-22B

EA-22A

EA-22B

Advantages

Aluminum panel with the sand blast treatment

Pure copper plating nickel button

500,000 times mechanical test

•Installation

SMQT

EA-22A

EA-22B



•*Dimension*

EA-22A

EA-22B

•*Packaging & shipping*

SMQT

• *Office show*

SMQT

• *Exhibition*

SMQT

2011 Brazil Fair
2012 Shenyang Fair
2013 Jinan Fair
2013 Shenzhen Fair
共赢
.....
2012 Shenyang Fair
2013 Shenyang Fair
2013 Shenzhen Fair
2015 Shenzhen Fair