Converter USB to RS485

Compatible with EIA/TIA RS-232,RS-485 standard

Interface:USB interface

RS-485 interface

Transmission medium:normal cables,twisted-pair cables or shielded cables

57.6kbps in 1200m transmission speed(short distance can reach 230kbps)

Transmission distance:5m(USB port)

1200m(RS485 port)

7-12V input voltage

SMQT®

• Parameter

SMQT®

□□□□□	
□□□□□□ □□□	□□□□□ □□□□□□□□□ □□□ USB □□□ RS485
□□□□□	EA-02
□□□	94 × 35 × 18 (□□□)
□□□□□□□ □□□□	□□ □□□□□□□ □□□□□ EIA / TIA RS-232C□ RS-485 □□□□□□□□
□□□□□□□□□□ □□□□□	□□□□ USB□ DB9 □□□□□□ □□□□□ RS-485 □□□□□□□ DB9 □□□□ □□ □□□□□□ □□□□ □□□□□ □□□□)).
□□□□□ □□□□□	□□□□□□□□ □□□ □□□□□□ □□□
□□□□□□□□ □□□□□□	□□□□□ □□□□ □□ □□□ □□□□□□□□ □□□□□ □□
□□□□□□ □□□□	57.6 □□□kbps (230 □□□ □□□ □□ □□□□□kbps 1200 □□□□□□□ □□ (□□□□M
□□□□□□ □□□	5 □□□□□) □ USB) 1200 □ (RS-485 □□□□)
□□□□□	□□□□□ □□□
□□□□□□□	□□□□□□ □□ □□□□□□ □□□□
□□□□□□□ □□□□□□□	5□ ~ 95□
□□□□□□ □□□□□□□□□□	-10 ℃ ~ 85 ℃
□□□□□ □□□□	□□□□
□□□□□□ □□□□□	0.116kg

• In-kind shooting

SMQT®

•*Feature*

SMQT

EA-02

Converter USB to RS485 Interface compatible with EIA / TIA RS-232C, RS-485 standard

Electrical Interface:

USB port, DB9 female connector
RS-485 side, DB9 male connector

Transmission rate:

Up to 57.6kbps (close up to 230kbps rate) in the 1200m distance

Transmission distance:

5 m (USB end) 1200 m (RS-485 terminal)

Suitable for data transmission system

0.116kg weight

Welcome OEM and 2 years quality warranty

• Application

SMQT

• Packaging & shipping

SMQT

□□□□□□□□ □□□□□□□ □□□□□	
□□□□□□ □□□	□□□□□ □□□□□□□□ □□□ USB □□□ RS485 EA-02
□□□□□□	100pcs □□□□□□□ □□ □□□□
□□□□□□ □□□□□ □□□	53 * 40 * 37 (□□)
□□□	12kg □

• *Office show*

SMQT

• *Exhibition*

SMQT