

● Parameter

SMQT

Interface	Supports EIA / TIA RS-232 and RS-485.
Connectors	Supports USB and DB9 (RS-485) connectors.
Protocol	Supports RS-232 and RS-485 protocols.
Transfer Rate	57.6 Kbps (1200 baud rate, 230 characters per second)
Length	5 meters (USB to 1200 baud rate (RS-485))

● Introduction

SMQT

This is a USB to RS485 converter. It converts USB to RS485.

It contains an ASIC (ASIC) and a USB controller.

RS-485 7 pins, 12V ~ 12V + 5V

98 pins / ME Windows 2000 / XP

Supports v5.0

Supports USB V1.1 and USB CDC V1.1

USB to RS485

Supports USB to RS485 conversion, RS485 to USB conversion, RS485 to RS485 conversion.

Supports RS485 to RS485 conversion.

57.6 Kbps (1200 baud rate, 230 characters per second) 1200 baud rate

Supports TIA / EIA RS-485

Supports RS485 to RS485 conversion

Supports RS485 to RS485 conversion (RS-485 to RS485 485 32 pins)

● Dimension Picture

SMQT



● Installations

SMQT

Switch Power supply



Door release button



Standalone Access controller



PC

Converter(USB to RS 485)

EA-02



● Features



1. 內建 ASIC 晶片 USB 通訊埠 支援 10/100Mbps
 / 2.0 埠 支援 10/100Mbps 通訊埠 USB1.1
 2. 支援 460800 碼元 碼元 碼元 碼元
 3. 支援 128 碼元 碼元 TX / RX 512 碼元
 4. 支援 10/100Mbps 埠 埠 埠 埠
 5. 支援 10/100Mbps 埠 埠
 6. 支援 WIN95 / 98 / 98SE / ME / 2000 / XP / NT3.5 系統
 7. 支援 埠 埠 埠 埠 USB 埠 埠 埠 埠
 8. 支援 埠 埠 埠 埠 埠 埠
 9. 支援 埠 埠 埠 埠

● Packing list



數量	100 / 單位
產品尺寸 (mm)	53L * 40W * 36.5H (mm)

● Office



● Exhibitions



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....