

● Parameter

SMOT®

規格仕様書	
製品名	高精度 温度センサー 温度計測器 温度計測器 温度計測器
型番	27-0000
寸法	86 86 * W * H) 20 mm
動作電圧	3A 12 @ 温度計測器 温度計測器VDC 36VDC 温度計測器
動作電流	温度計測器 温度計測器 温度計測器 温度計測器 温度計測器
動作電圧	0V/NC/温度計測器 COM
動作電流	温度計測器 温度計測器 500,000 温度計測器
動作電流	温度計測器 温度計測器 温度計測器 温度計測器 温度計測器 温度計測器
動作電流	--10 °C ~ + 50 °C
動作電流	0-95% (温度計測器 温度計測器)
動作電流	温度計測器 温度計測器 温度計測器
動作電流	0.09 mm
動作電流	100/温度計測器

● Introduction

SMOT®

00000 0000 00000000 00000000 00000000 00000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
 0000000000 00000000 0000 0000000000

□□□□□□ □□□□□□ □□□□□□ □□□□□□.

[illegible]

000000 00000000 00000000 000000 00 000000 000000 000000 000000.

XXXXXXXXXX XXXXXXXX XXXXXX XX XXXXXX XXXXX XXXXXX XXXXX
XXXXXXXXXX XXXXXXXXXXXX XXXXXXXXXXXX XXXXXXXXXXXX XXXXXXXXXXXX.

● Dimesion Picture

SMOT®

Switch Power supply



Door release
button EA-27



Converter
(RS232 to RS485)



Standalone
controller



PC



THE ONE *Strong stability*

PC rubber seal lock core,
resistance to heat shock,
500, 000 times mechanical test
qualified, suitable for all
Access control system



THE SECOND *Superior Design*

Simple and beautiful appearance,
stainless steel wire drawing
panel.

● Packing list

SMQT

SMQT 门禁读卡器 包装清单	
门禁读卡器 1个	门禁读卡器 1个 LED
包装清单	100/个
包装尺寸 (长 * 宽 * 高)	46.5 37.5 * (W * 28 (H) (mm))
包装重量 (kg)	10.1 (kg)





● In the Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair