
● Parameter

SMQT

□□□□□□	
□□□ □□□□□□	□□□□ □□□ □□□□□□
□□□□□□	EB-121
□□□	110 * 58 * 22 (□□□)
□□□	0.15KG
□□□□□□□□ □□□□□ □□□□□□□□	12V □□□□□□□□
□□□□□ □□□□□	□□□□□□ □□□ □□□□□□
□□□□□□□□ □□□□ □□□□□□	-10 ° C ~ + 50 ° C
□□□ □□□□□	WIRLESS □□□□□□ □□□□□ □□□□

● Introduction

SMQT

Wireless Transmission Repeater

enlargement wireless transmission



*Blow up scope
50-100mm*



Suitable for wireless homw alarm system







Expanding wireless signal transmission distance of 50-100 m.

Suitable for all Wireless frequency.

AC adapter standard optional.

EB-121

Used in home wireless security system.

Pacakgaing	
EB-121	EB-121
25PCS /	25PCS /
43 * 30 * 36 (mm)	43 * 30 * 36 (mm)
10KG	10KG



● Office

SMQT®



● Exhibitions

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair