Parameter

SMQT

□□□□□□□ □□□	DC12V
□□□□□□ □□□□□ □□□□□	15W
□□□□□□□ □□□□	□□□□□□ ABS □□□□□□ □□□□□
□□□□□□ □□□□□□□	800 □□□□ □□□□ 15 ~ □□□□
SNR	≥82db
□□□□□□ □□□□□ □□□□□□	150db
□□□□□ □□□□□ □□□□	-10 ℃ ~ 65 ℃
□□□□□	40 □ 95 □□□ □

Introduction

SMQT

□□□□□□ □□ NV020S □ □□□□□□ □□□□□□□□ □□□□□□□□ □□□□□□ □□ □□□□ □□ □ □□□□□ □□□□□ □□□ □□□□□□ □□□□
□□□□□ □□□□□ ABS □ □□□□□□ □□ □□□□□□□ □□□□□□□ □ □□□□ □ □□□□□ □□ □□□□□□□ □ □□□□□□ □□□□□□ □□□□□□
□□ □□□□□□□ □□□□□□ □□□□□ □□□ □□□□□□ Philips □ □ □□□□□□ □□□□□ □ □□□ □□□□
.□□□□□□ □□□□□□□□ □□□□□□ □□□□□□□□□□ □ □□□□□□ □□□□□□□ □□□□
□□□ □□□□ □□□□□□ □□□□ □ □□□□□□ □ □□□□□□□ □ □□□□□□ □□□□□ □ □□□□□ :□□□□□□.
115 □□□□□□□ □□□□□ □□□□□□□ □□□□□ □□ □□□□□□□□□□□ □□□□□□□ □□□□□□db □□□□□□ □□□□□ □□ □□□□□□□□□
□□□□□□ antif.

Dimesion Picture

SMQT

Features

SMQT

1

Fire-proofing materials

Fire—proofing materials

High-strength fire retardant ABS material, the surface spray processing, durable, long service life .

2

Alarm sounds great

Alarm sounds great

NV020S do use voice chip voice processing core, with industrial-grade performance and stability of the reticle;

Built-in dual output Philips audio amplifiers, loud, high definition .

3

Rotating stents

Rotating stents

Single power supply, effective utilization of power usage.

It can set on the floor or wall, 90' Rotating stents.

4

Wide applicability

Wide applicability

High-strength fire retardant ABS material, the surface spray processing, Scope: oil, high pressure, mines, toxic, airport bird and so on.

Packing list

SMQT

□□□□□□	50 / □□□□
□□□□□□□□ □□□□□□□ □□□□□□□	57 * 57 * 23.5 (□□)
□□□□□□□ □□□	16.46Kg

Office

SMQT

Exhibitions

SMQT