

● Parameter

SMQT

電圧	DC12V
消費電力	15W
対応規格	自動車 ABS 対応規格
周波数帯域	800 Hz ~ 15 kHz
SNR	≥82db
音圧	150db
動作温度範囲	-10 °C ~ 65 °C
寸法	40 x 95 mm

● Introduction

SMQT

このスピーカーは NV020S と呼ばれ、自動車用の ABS 対応規格に適合している。また、15W の消費電力を必要とせず、800 Hz ~ 15 kHz の周波数帯域をカバーしている。SNR は ≥82db、音圧は 150db を実現している。動作温度範囲は -10 °C ~ 65 °C であり、40 x 95 mm のコンパクトなサイズで、115 dB の音圧を実現している。また、antif. の機能を備えている。

● Dimesion Picture

SMQT





1

Fire-proofing materials

Fire-proofing materials

High-strength fire retardant ABS material, the surface spray processing, durable, long service life.



2

Alarm sounds great

Alarm sounds great

NV020S do use voice chip voice processing core, with industrial-grade performance and stability of the reticle;

Built-in dual output Philips audio amplifiers, loud, high definition.



3

Rotating stents

Rotating stents

Single power supply, effective utilization of power usage.

It can set on the floor or wall, 90° Rotating stents.



4

Wide applicability

Wide applicability

High-strength fire retardant ABS material, the surface spray processing, Scope: oil, high pressure, mines, toxic, airport bird and so on.

● Packing list

SMOT

□□□□□□	50 / □□□□
□□□□□□□□ □□□□□□□□ □□□□□□□□	57 * 57 * 23.5 (□□)
□□□□□□□□ □□□	16.46Kg



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....