

● Parameter

SMQT®

Parameter	
Model	EB-169
Voltage	DC12V DC24V
Flash frequency	90 times / minute
Operating voltage	9-15VDC 20-28VDC
Light source	LED
Power	12V≤80mA / 24V≤100mA
Power	2W 5W
Part number	0001000 (0001000 0001000 0001000) (0001000)
Size	72 * 42 (mm)

● Introduction

SMQT®



Combination of fixed base plate

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

Strobe indicator light

LED lights, flash frequency up to 90 times a minute.







Strobe Alarming light

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

LED guide plate

Select high-quality materials,
strict quality control, production
of exquisite workmanship.
This assures the mixer
durable products.



● Packing list

SMOT®

□□□□□□□□ □□□□□□ □□□□□	
□□□□□□ □□□	□□□□ □□□□□□□□ □□□□
□□□□□□□	100 □□□□ / □□□□ □□□□□□□□ □□□□
□□□□□□□ □□□□□ □□□	38.3 * 35.3 * 30.3 (□□)
□□□□	12kg □



● Office

SMQT®



● Exhibitions

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

