

Wired magnetic door contact sensor

NO/NC mode optional

20±5(mm) gap distance

MAX Voltage≤100VDC,MAX current≤500mA

Suitable for wooden door or window

Fireproof ABS shell,White/Brown color optional

Weight10g



• Parameter



品名	有线磁吸式门磁传感器
型号	EB-134
尺寸	24 × 41 × 6 (mm)
触点类型	NO / NC (可选)
间隙	20 ± 5 (mm)
额定电压	≤100V 直流
额定电流	≤500mA
额定功率	≤10W
外壳材料	ABS (阻燃) 白色 / 棕色
适用门框	木质门框 / 金属门框
适用温度	ABS 塑料适用温度范围
工作温度范围	-10 °C ~ 50 °C
重量	10G

• In-kind shooting





• *Feature*

SMQT



EB-134

Dimension:24×41×6(mm)

NO/NC mode optional(default is NC mode)

20±5(mm) Gap

MAX voltage≤100VDC,MAX current≤500mA

Suitable for Wooden door or window

Fireproof ABS material shell

White/Brown color optional

Weight 10g

Welcome OEM, 2 years quality warranty

•Packaging & shipping

SMQT

□□□□□□□□ □□□□□□ □□□□□□	
□□□□□□ □□□□	EB-134
□□□□□□	1600 □□□□□□ □□ □□□□ □□□□□□ □□□□
□□□□□□ □□□□□□ □□□□	38 * 30 * 30 (□□)
□□□□	20 □□kg



WE LOGISTICS



• Office show

SMQT



• Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair