2020□COVID-19□□□□□□□□□□□□□□□□□□□□□□□□□□□□



Dynamic facial Reader

with face temperature and mask checking

MF-1008□□□□□

□□□□	2020□COVID-19□□□□□□□□□□□□□□□□□□□□□□□□□□□□	
□□	**MF-1008A**	**MF-1008B**
□□		
□□□□□	Hi3516DV300	
□□	Linux□□□□	
□□□□□	16G EMMC	
□□□□□	1 / 2.7□□CMOS	
□□	4.5□□	
□□	7□TFT	
□□□□□□	600 * 1024	
□□	16□9	
□□□□	□□□□□□□□□□□□	
□□□□	□□8Ω/ 2□	
□□□□		
□□	□□□□□□□□□□	
□□□□	2□□□1920 * 1080	

□□□□□	□□0.01Lux @ F1.2□ICR□;□□0.001Lux @ F1.2	
□□□	≥50db□AGC□□□	
□□□	≥80□□	
□□□□		
□□	1.2-2.2 M□□□□□	
□□	0.5-2□	
□□□□	□□±40□	
Reco□□□	<500ms	
□□	□□22400□□□□□□100000□□□	
□□		
□□	30-45□℃□	
□□□	±0.5□℃□	
□□	40□	
□□□□	<500ms	
□□		
□□□□	RJ45 10M / 100M□□□	
□□□	□□□□/□□26□34	
□□□□	1□□□□□□	
USB□□	1USB□□□□□□□□□ID□□□□	
□□		
□□□□	□□12V / 3A	
□□□□	20W□□□□	
□□□□	-15℃□+ 60℃	
□□	5□90□□□□□	
□□	123.5□□□* 45.5□□□* 266□□□mm	123.5□□□* 45.5□□□* 266□□□mm
□□	1.9□□	2.1□□

□□□□□ MF-1008 □□

Size



Model:MF-1008A

:mm

Model:MF-1008B

:mm

Device Feature

10 system languages and voice adjustable

Celsius and Fahrenheit temperature display adjusable



Wire interface introduction

J1	WG Output:Orange D0,White D1,Green GND
	WG Input: Brown&White D0,Yellow D01,Grey GND
	Alarm Out:Brown Alarm+ ,Purple Alarm-(I/O Signal)
	RS485: Yellow&White 485+ ,Blue&White 485-
J2	RJ45 Network interface(100M)
J3	Power Supply (10-15V/3A)

MF-1008A



MF-1008B

Browser software interface



Body temperature detecting in live

MF-1008A

MF-1008B

Temperature measurement range 30-45 *(℃)* Accuracy ± *0.5(℃);*

Automatically identify unmasked personnel and provide real-time warning;

Support mid-range temperature measurement and real-time warning of high temperature;

Support temperature data SDK and HTTP protocol docking;

Support binocular live detection;

Unique face recognition algorithm to accurately recognize faces, face recognition;

time <500ms;

Adopt Linux operating system for better system stability;

IP34 rated dust and water resistant;

MTBF> 50000 H;

Support 22400 face comparison library and 100,000 face recognition records;

Support one Wiegand input or Wiegand output;

Pacakages



Optional Bracket

A bracket
For MF-1008B

B bracket
For MF-1008B

C bracket
For MF-1008B

D bracket
For MF-1008A

Access control &Time attendance

Apply to a variety of access control and time attendance sites, such as factories, offices, schools, supermarkets, and so on.

□□□□□□

11:56:48

16 18
X101

2019-11-04 Mon
16:11
X108

17:23 08

23:48 26