




2020 2020 COVID-19



Dynamic facial Reader

with face temperature and mask checking





MF-T1008

	2020 COVID-19	
	MF-1008A	MF-1008B
	Hi3516DV300	
	Linux	
	16G EMMC	
	1 / 2.7 CMOS	
	4.5	
	7 TFT	
	600 * 1024	
	16 9	
	8Ω/ 2	
	2 1920 * 1080	

照度	≥0.01Lux @ F1.2ICR;≥0.001Lux @ F1.2	
噪音	≥50dbAGC	
快门	≥80	
镜头		
焦距	1.2-2.2 M	
光圈	0.5-2	
精度	±40	
Reco	<500ms	
像素	22400100000	
温度		
工作	30-45℃	
精度	±0.5℃	
快门	40	
精度	<500ms	
接口		
网络	RJ45 10M / 100M	
存储	/2634	
接口	1	
USB	1USBID	
电源		
电压	12V / 3A	
功率	20W	
温度	-15℃+ 60℃	
重量	590	
尺寸	123.5* 45.5* 266mm	123.5* 45.5* 266mm
厚度	1.9	2.1

摄像头 MF-T1008

Size




Device Feature

10 system languages and voice adjustable

English
繁体中文
русский
Deutsch
Le français
한국어
Português
Espanol
lingua italiana
日本の


Celsius and Fahrenheit temperature display adjustable



Wire interface introduction



Browser software interface



Body temperature detecting in live



MF-1008A



MF-1008B

Temperature measurement range 30-45 (°C) Accuracy $\pm 0.5(^{\circ}\text{C})$;

Automatically identify unmasked personnel and provide real-time warning;

Support mid-range temperature measurement and real-time warning of high temperature;

Support temperature data SDK and HTTP protocol docking;

Support binocular live detection;

Unique face recognition algorithm to accurately recognize faces, face recognition;
time <500ms;

Adopt Linux operating system for better system stability;


IP34 rated dust and water resistant;

MTBF> 50000 H;

Support 22400 face comparison library and 100,000 face recognition records;

Support one Wiegand input or Wiegand output;


Packages



Optional Bracket



A bracket
For MF-1008B




0.55m

B bracket
For MF-1008B



1.1m

C bracket
For MF-1008B



1.3m

D bracket
For MF-1008A

Access control & Time attendance



Apply to a variety of **access control** and **time attendance** sites, such as factories, offices, schools, supermarkets, and so on.



