

## ● Parameter

SMQT

□□□□	86L * 86W * 39H□MM□
□□□□	DC12V
□□□□	NO / NC / COM
□□□□□	50□□□□□□□
□□□□	□□□□□□□
□□	-20°C□+ 50°C
□□□□	0□95□□□□□□□
□□□□	10□□
□□	100

## ● Introduction

SMQT

- 
- IP-55□□□□□/ SUS 304□□□□
- 
- 
- LED□□□□□□□□□□□□
- 1□□□□□□□□□□□□□□□□
- 2□□□□10cm□□□□□□□□□□
- IP-55
- 3A / 120V AC□30V DC
- DC 12V
- 20-55°C
- 10□□
- 85□
- 

## ● Dimesion Picture

SMQT



## ● Installations

**SMOT**



## ● Features

**SMOT**

**1 Durable and Reliable**  
more than 5 years life time

**2 Well-made**  
drawing panel, touch feeling is extraordinary

**4 Installation**  
easy install



**3 Welcome OEM**  
print logo

**5 Technology-leading**  
Anti-interference, induction distance is adjustable



□□	100 /□
□□□□	46.5L * 37.5W * 28H□□□□
□□□□	10.6□□

● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair