

 Parameter

SMQT®

□□□□	EA-82K□□□□□□□□□□
□□□□	DC12V±DC3V
□□□□	< 2W
□□□□	125KHZ ID
□□□□	60□□
□□□□	10000
□□□□	10000
□□□□	RS485
□□□□	9600□N□8,1□
□□□□	4MbitsFLASHMemory
□□□□	96L * 96W * 22H□MM□
□□□□	□□□□□□
□□□□	-30°C□+ 65°C
□□□□	□□□/□+□□/UID +□□/□□□□

Introduction SMQT®

SMOT®

TCP / IP RFID RS485 Connet software.It PC RFID

[illegible]

```
*[0][0][0][0][0][0][0][0][0][0][0][0][0][0];[0][0]breathingbackgroundLight[0][0][0][0][0][0][0][0][0][0]
```

*PC

```
*FLASH10
```

* 100

[illegible]

*7

[illegible][illegible]

*WG WG26 / 34

***IP67**

*□□□□□□□□□□□□□□□□□□□□

[illegible]

*□□□□□□□□□□□□□□□□□□



● Dimesion Picture

SMQT



● Installations

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

