

● Parameter

SMQT

□□	
□□□□	□□□□□□□□
□□	EB-169
□□□□	DC12V DC24V
□□□□	90□/□□
□□□□	9-15VDC 20-28VDC
□□	LED□□□
□□□□	12V≤80mA/24V≤100mA
□□□	2W 5W
□□	≥1000□□□□□□□□□□□□
□□	72 * 42□□□□

● Introduction

SMQT



*Combination of fixed base plate*

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

*Strobe indicator light*

LED lights, flash frequency up to 90 times a minute.



---

● Dimesion Picture

**SMQT**



---

● Features

**SMQT**



## *Strobe Alarming light*

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

## *LED guide plate*

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



### ● Packing list

**SMOT**

	□□□□
□□□□	□□□□□□□□
□□	100□/□
□□□□	38.3 * 35.3 * 30.3□□□□
□□	12□□



● Office

SMQT



● Exhibitions

SMQT



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair