

● Parameter

SMQT

|      |                    |
|------|--------------------|
| □□   |                    |
| □□□□ | □□□□□□□□           |
| □□   | EB-169             |
| □□□□ | DC12V DC24V        |
| □□□□ | 90□/□□             |
| □□□□ | 9-15VDC 20-28VDC   |
| □□   | LED□□□             |
| □□□□ | 12V≤80mA/24V≤100mA |
| □□□  | 2W 5W              |
| □□   | ≥1000□□□□□□□□□□□□  |
| □□   | 72 * 42□□□□        |

● Introduction

SMQT



*Combination of fixed base plate*

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

*Strobe indicator light*

LED lights, flash frequency up to 90 times a minute.



---

● Dimesion Picture

**SMQT**



---

● Features

**SMQT**



## *Strobe Alarming light*

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

## *LED guide plate*

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



### ● Packing list

**SMOT**

|      |                        |
|------|------------------------|
|      | □□□□                   |
| □□□□ | □□□□□□□□               |
| □□   | 100□/□                 |
| □□□□ | 38.3 * 35.3 * 30.3□□□□ |
| □□   | 12□□                   |



● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....