

Wired metal magnetic contact sensor

NO/NC Code mode optional

50±10(mm) gap distance

Max voltage≤100V DC,Max current≤500mA

Suitable for metal door or window

Material:mode A is Alloy-zn

mode B is ABS

Silver color

Weight:mode A 158g,mode B 62g



Parameter

SMQT

□□	
□□□□	□□□□□□□□□□
□□	EB-139
□□	106×16×16□mm□
□□□□	NO / NC□□□□
□□	50±10□mm□
□□□□	≤100VDC
□□□□	≤500mA
□□□□□	≤10W
□□	□□□
□□	□□□□□
□□	A.alloy-zn□B.ABS
□□	A□158g / B□62g

In-kind shooting

SMQT



• *Feature*

SMQT



EB-139A



EA-139B

Wired magnetic contact sensor

NO/NC code mode optional

50±10(mm) gap distance

MAX voltage:≤100V DC,MAX current≤500mA

Material: mode A:Alloy-zn, mode B:ABS

Suitable for metal door or window

Color:grey silver

Weight: mode A:158g mode B:62g

Welcome OEM and 2 years quality warranty

● *Packaging & shipping*

SMQT

	□□□□
□□□□	□□□□□□□□EB-139
□□	200pcs /□
□□□□	37×30×20□cm□
□□	26□37kg



WE LOGISTICS



• Office show

SMQT



• Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....