

Wiegand 26 SM713.56MHz CPU



13.56MHz CPU	
Model	Wiegand 26 SM713.56MHz CPU
Dimensions	96mm*96mm*22mm
Voltage	9VDC-16VDC
Current	≤120mA
Frequency	13.56MHz
Response time	<0.1s
Material	PC
Temperature range	3.5℃-5.5℃
Humidity	< 100%
Interface	Wiegand 26
Power supply	±15v
Operating temperature	0℃-60℃
Storage temperature	-20℃-70℃

Wiegand 13.56MHz CPU



Support CPU SHC1112 card

Support the ISO14443a protocol

Card number and key can be user-defined

Fully sealed design epoxy seal and waterproof type

Wiegand 26 communication interface, 26-122 bit output

□□□□□




CPU Card Reader



GND	9-16V DC	D0	D1	Buzzer	LED	RS232-TX	RS232-RX
-----	----------	----	----	--------	-----	----------	----------

Can work with different access control accessories :



Power Supply



EM Lock



Bluetooth Door Button



Dual Doors Access Control



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技




SMQT[®]
铭汗科技





□□



□□

2011 Brazil Fair



2012 shen yang Fair




2013 Jinan Fair



2013 Shenzhen Fair



2017 Shenzhen Fair



2012 shen yang Fair



2013 shen yang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair





1111

[illegible][illegible][illegible]

□□□□**1-3**□□□□□□□□□□**10-15**□□□□

[illegible][illegible]

