

# Wired magnetic contact sensor

Fireproof ABS material shell

NO/NC model optional

Brown/white color optional

20±5(mm) gap distance

Suitable wooden door or window

14g weight

**SMQT**



|    |                 |
|----|-----------------|
| 型號 | NO / NC 常開 / 常閉 |
| 型號 | EB-132          |
| 尺寸 | 34 * 41 * 6.5mm |
| 型號 | NO / NC 常開 / 常閉 |
| 尺寸 | 20±5mm          |
| 電壓 | ≤100VDC         |
| 電流 | ≤500mA          |
| 功率 | ≤10W            |
| 材質 | ABS             |
| 溫度 | -10℃~50℃        |
| 重量 | 14g             |

SMQT

# PRODUCT FEATURE



EB-132

Dimension:34×41×6.5(mm)

NO/NC mode optional

20±5(mm) distance gap

MAX voltage≤100VDC,MAX current≤500mA

Fireproof ABS material shell

White/Brown color optional

Suitable for wooden door or window

14g weight

2 years quality warranty,welcoem OEM



# PRODUCT PICTURE



□□□□



□□□□





□□



□□





|                       |                                                                |
|-----------------------|----------------------------------------------------------------|
| <b>Trade terms:</b>   | <b>EXW</b>                                                     |
| <b>Payment terms:</b> | <b>T/T, Western union, Paypal etc</b>                          |
| <b>Delivery time:</b> | <b>Normal order within 7 days, bulk order 10-15days</b>        |
| <b>Packing:</b>       | <b>Neutral paper box and paper carton</b>                      |
| <b>Shipping:</b>      | <b>Express company or by sea, by air or appointed by buyer</b> |