

Wired magnetic contact sensor

- NC/NO code mode optional
- 20±5(mm) gap distance
- MAX voltage≤100V DC,MAX current≤500mA
- Suitable for wooden door or window
- Fireproof ABS material shell
- White/Brown color optional
- 8g weight



□□□□

□□	
□□□□	□□/□□□□□□□□□□□□□□
□□	EB-135
□□	24×41×6□□□□
□□□□	NO / NC□□□□
□□	20±5□□□□
□□□□	≤100VDC
□□□□	≤500mA
□□□□	≤10W
□□	□/□□□□
□□	□□□□
□□	□□ABS□□
□□□□	-10℃□50℃
□□	8□

□□□**EB-135**□□□□□□□□□□

2 Color optional



White

Brown

Fireproof ABS housing

Brown or White color optional

Suit for wooden doors or windows

Normal open or Normal close optional

2 years quality warranty,welcome OEM

□□□□

IN-KIND□□






Door

Magnetic Contact

safe door happy life

(Notice:need match the home alarm system to



Sash window

In window close status, door magnetic host and magnetic stripe respectively embedded in the two Windows, do not to leave a gap between, open the window after the success of alarming, Then to fixed.



Sliding window

In window close status, door magnetic host and magnetic stripe respectively embedded in the two Windows, do not to leave a gap between, open the window after the success of alarming, Then to fixed.



Notice:
Gap<2cm

2 Color optional



White



Brown





□□□□



□□□□

□□□□□



□□



□□

2011 Brazil Fair



2012 shen yang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 shen yang Fair



2013 shen yang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair





00000000 0000 C00000000000 0000 00

0000000000

2.000000T / T0000000000

3.24000000 0 00d0 00000000000000

000000000000000000000000000000

5.00000000 00 0UPS0DHL0TNT0Fedex0000000000

00000

00000

00 000000000000

000000000000000000000000000000 00000000

000000000000

000000001-30000000000000000010-15000000

0000000000000000

A000000000

00000000000000000000

000000000000000000000000000000 0000 0000

000000000000000000000000

000000000000000000000000000000 0000000 0 00000000000000 00000000 000000ñ

000000 00000000 000000ñ