

Converter USB to RS485

Compatible with EIA/TIA RS-232, RS-485 standard

Interface: USB interface

RS-485 interface

Transmission medium: normal cables, twisted-pair cables or shielded cables

57.6kbps in 1200m transmission speed (short distance can reach 230kbps)

Transmission distance: 5m (USB port)

1200m (RS485 port)

7-12V input voltage

SMQT®



• Parameter

SMQT®

Nombre del producto	Convertidor USB a RS485
Modelo	EA-02
Dimensión	94 x 35 x 18 (mm)
Característica serie	Interfaz compatible con EIA / TIA RS-232C, estándar RS-485
Interfaz Eléctrica	Puerto USB, conector hembra DB9, lado RS-485, conector DB9 macho con terminal (cinco cables).
Manera de trabajar	Asíncrono semidúplex
Medio de transmision	Línea común, par trenzado o cable blindado
Velocidad de transmision	Hasta 57.6kbps (cerca de la tarifa de 230kbps) en la distancia de 1200m
Distancia de transmisión	5 m (extremo USB) 1200 m (terminal RS-485)
Color	gris
Uso	Sistema de control de acceso
Humedad relativa	5% ~ 95%
Entorno temprature	-10 °C ~ 85 °C
carta de acuerdo	Transparente
Peso neto	0.116kg

• Introduction

SMQT®

El convertidor del USB al RS485 para el software del sistema del control de acceso de la puerta funciona en la computadora.



• *Feature*

SMQT



Converter USB to RS485
Interface compatible with EIA
/ TIA RS-232C, RS-485 standard

Electrical Interface:

USB port, DB9 female connector
RS-485 side, DB9 male connector

Transmission rate:

Up to 57.6kbps (close up to 230kbps
rate) in the 1200m distance

Transmission distance:

5 m (USB end) 1200 m (RS-485 terminal)

Suitable for data transmission system

0.116kg weight

Welcome OEM and 2 years quality warranty

switch power supply



Door release button



Access control keypad

Converter USB to RS485 EA-02



PC

• Office show

SMQT®



• Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

