

Especificación	
Nombre del producto	Luz estroboscópica alarmante con cable
Modelo	EB-169
Tensión nominal	DC12V DC24V
Frecuencia intermitente	90 latidos / min
Tensión de funcionamiento	9-15VDC 20-28VDC
Camino ligero	Luces LED brillan
Corriente de trabajo	12V≤80mA / 24V≤100mA
Luces de encendido	2W 5W
Vida	≥1000 horas (operación continua de potencia estándar)
Talla	72 * 42 (mm)



*Combination of fixed base plate*

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

*Strobe indicator light*

LED lights, flash frequency up to 90 times a minute.



---

● Dimesion Picture

**SMQT**



---

● Features

**SMQT**



## *Strobe Alarming light*

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

## *LED guide plate*

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



### ● Packing list

**SMOT**

<b>Lista de embalaje</b>	
Nombre del producto	Alarma cableada Sluz trobe
Cantidad	100 piezas / caja
Tamaño del cartón	38.3 * 35.3 * 30.3 (cm)
Peso	12 kg



● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair