

Touch door release button

LED light indication

Touch iduction

Plexiglass panel

2 sizes optional

500000 times mechanical test.

SMQT



• Parameter

SMQT

Parámetro	
Nombre del producto	LED de la puerta de atrás la luz botón del interruptor
Modelo	EA-20
Dimensión	Modelo A: 86 × 56 × 25 (mm) Modelo B: 86 × 86 × 25
Voltaje de entrada	DC 12V
estructura estándar	tocar plexiglás
ensayo mecánico	prueba de 500.000 veces
rango adecuado	puerta hueca
Color	panel negro, marco de la astilla
Uso	sysetm control de acceso y de interfono sistema
Humedad relativa	0 ~ 95%
temprature Medio Ambiente	-20 °C -50 °C
Peso neto	Modelo A: 0.06kg Modelo B: 0.09kg

• Introduction

SMQT





EA-20A




EA-20B

1 Superior Design

Touch push button design simple and beautiful, Panel using organic glass materials, touch induction to open the door, button USES the interactive design of light touch response. Internal using PC rubber production, high temperature resistant do not fade

Resistance to heat shock Organic glass touch responsive



2 Product components

500,000 times test qualified, the relay switch power output, (NO NC COM)3 lines button suitable for all Access control system

NO NC COM, 3 lines

3 Strong stability

Waterproof and dustproof more durable and strong, resistance to high temperature shock do not fade.

Waterproof and Dustproof Stable solid long life



• Application

SMQT®



Switch Power Supply



• Packaging & shipping

SMQT®

lista de embalaje	
Nombre del producto	EA-20 LED de la puerta de atrás la luz botón del interruptor
Cantidad	100 PC por el cartón
Tamaño del cartón	37 * 30 * 29 (cm)
Peso	12kg



WE LOGISTICS



• Office show

SMQT



• Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair