

spécification	
Nom du produit	Lampe stroboscopique d'alarme filaire
Modèle	EB-169
Tension nominale	DC12V DC24V
Fréquence de clignotement	90 battements / min
Tension de fonctionnement	9-15VDC 20-28VDC
Manière légère	Les lumières LED brillent
Courant de travail	12V≤80mA / 24V≤100mA
Lumières de puissance	2W 5W
La vie	≥1000 heures (fonctionnement continu de puissance standard)
Taille	72 * 42 (mm)



Combination of fixed base plate

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

Strobe indicator light

LED lights, flash frequency up to 90 times a minute.







Strobe Alarming light

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

LED guide plate

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



● Packing list

SMOT

Liste d'emballage	
Nom du produit	Alarme filaire Slumière trobe
Qté	100 pièces / boîte
Taille du carton	38,3 * 35,3 * 30,3 (cm)
Poids	12Kg



● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair