

Wired metal magnetic contact sensor

NO/NC code mode optional

50±10(mm) gap distance

Max voltage ≤100VDC, Max current ≤500mA

Alloy-zn material

Suitable for metal door or window

Grey color

Weight : A:150g B:100g C:50g

SMQT®



• Parameter

SMQT®

Modèle	EB-138A	EB-138B	EB-138C
Dimensions	46 * 21 * 12 (mm)	47 * 17 * 7 (mm)	30 * 13 * 6 (mm)
Connexion	Normalement ouvert / normalement fermé	Normalement ouvert / normalement fermé	Normalement ouvert / normalement fermé
Distance de fonctionnement	50 ± 10 (mm)	50 ± 10 (mm)	50 ± 10 (mm)
Pression maximale	≤100VDC	≤100VDC	≤100VDC
Puissance de travail	≤ 10W	≤ 10W	≤ 10W
Matériau du boîtier	alliage de zinc	alliage de zinc	alliage de zinc
Portée	Porte ou fenêtre en fer	Porte ou fenêtre en fer	Porte ou fenêtre en fer
Courant de charge	≤500mA	≤500mA	≤500mA
Poids du produit	150 g	100g	50 grammes

• Introduction

SMQT®

Le contacteur magnétique de contact de porte est le capteur de porte magnétique pour le système de contrôle d'accès de porte magnétique et le système d'alarme de porte magnétique.

PRODUCT PICTURE



• *Feature*

SMQT

PRODUCT FEATURE



Wired metal magnetic contact sensor

NO/NC code mode optional

50±10 gap distance

Max voltage:≤100V DC, Max current≤500mA

Max rating≤10W

Alloy-Zn material

Suitable for metal door or window

Weight: A:150g B:100g C:50g

Welcome OEM, 2 years quality warranty



• Office show

SMQT®



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair