Parameter

SMQT

Nome del prodotto	Outdoor sensore del fascio impermeabile
Numero di modello	ABT
tensione di esercizio	13.8 ~ 24VDC 11 ~ 28VAC
Corrente di funzionamento	40-65mA
velocità indicazione	50 ~ 700 m / sec
uscita anti-demolizione	NC
temperatura ambiente	-20 ℃ ~ + 50 ℃
uscita di allarme	NO / NC
regolazione del livello	180 ° ± 90 °
regolazione Vertocal	± 10 °
Colore	Nero
Materiale	resina PC

Introduction

SMQT

PRODUCT PICTURE

Il rilevatore di movimento barriera a raggi infrarossi viene utilizzato sul recinto

come il lavoro a infrarossi rilevatore di recinzione con il sistema di allarme.

•Dimension

SMQT



•Feature

SMQT

PRODUCT FEATURE

Sealed integration structure is able to work inthe has enviroment

Automtically regulate to confranted with fog or inclement weathe

Sensitivity(AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built -in integrate optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes,low-power digital

•*Packaging & shipping*

SMQT

• *Office show*

SMQT

• *Exhibition*

SMQT

2011 Brazil Fair
2012 Shenyang Fair
2013 Jinan Fair
2013 Shenzhen Fair
共赢
.....
2012 Shenyang Fair
2013 Shenyang Fair
2013 Shenzhen Fair
2015 Shenzhen Fair