

● Parameter

SMQT®

Tensione operativa	DC12V
Potenza di uscita nominale	15W
Materiale dell'alloggiamento	Materiali ignifughi in ABS
Risposta in frequenza	800HZ ~ 15KHZ
SNR	≥82db
Volume di uscita	150dB
Temperatura di lavoro	-10 °C ~ 65 °C
Umidità	Dal 40% al 95%

● Introduction

SMQT®

NV020S utilizza un core di elaborazione vocale con chip vocale, con prestazioni di livello industriale e stabilità del reticolo;

Materiale ABS ignifugo ad alta resistenza, trattamento spray superficiale, lunga durata e lunga durata;

Amplificatori audio Philips a doppia uscita integrati, ad alta definizione;

Singolo alimentatore, utilizzo efficace del consumo di energia;

Campo di applicazione: petrolio, alta pressione, mine, tossici, uccelli aeroportuali e così via.

La sirena elettronica è la sirena smail di allarme 115db utilizzata con l'allarme antincendio e l'allarme antif.

● Dimesion Picture

SMQT®





1

Fire-proofing materials

Fire-proofing materials

High-strength fire retardant ABS material, the surface spray processing, durable, long service life.



2

Alarm sounds great

Alarm sounds great

NV020S do use voice chip voice processing core, with industrial-grade performance and stability of the reticle;

Built-in dual output Philips audio amplifiers, loud, high definition.



3

Rotating stents

Rotating stents

Single power supply, effective utilization of power usage.

It can set on the floor or wall, 90° Rotating stents.



4

Wide applicability

Wide applicability

High-strength fire retardant ABS material, the surface spray processing, Scope: oil, high pressure, mines, toxic, airport bird and so on.

● Packing list

SMOT

Quantità	50 / scatola
Specifiche dell'imballaggio	57 * 57 * 23.5 (cm)
Peso dell'imballaggio	16.46Kg



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....