## Parameter

SMQT

| specificazione | |
|---|---|
| Nome del prodotto | Luce stroboscopica allarmante cablata |
| Modello | EB-169 |
| Tensione nominale | DC12V DC24V |
| Frequenza lampeggiante | 90 battiti / min |
| Tensione operativa | 9-15VDC 20-28VDC |
| Modo leggero | Le luci a LED si illuminano |
| Corrente di lavoro | 12V≤80mA / 24V≤100mA |
| Luci di potenza | 2W 5W |
| Vita | ≥1000 ore (funzionamento continuo con alimentazione standard) |
| taglia | 72 * 42 (mm) |

## Introduction

SMQT

## Dimesion Picture

SMQT

## Features

SMQT

## Strobe Alarming light

1.Suitable for higher-end stroboscopic system model.
2.Chimney texture design improves the light diffusion effect.
3.Flash 90 times per minute.
4.The high-quality LED light.
5.IP44 protection grade.
6.AS+ABS shell.

## LED guide plate

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.

## Packing list

SMQT

| Elenco di imballaggio | |
|---|---|
| Nome del prodotto | Allarme cablato Sluce trobe |
| Quantità | 100 pezzi / scatola |
| Formato della scatola | 38,3 * 35,3 * 30,3 (cm) |
| Peso | 12Kg |

## Office

SMQT

## Exhibitions

SMQT

2011 Brazil Fair
2012 Shenyang Fair
2013 Jinan Fair
2013 Shenzhen Fair
共赢
.....
2012 Shenyang Fair
2013 Shenyang Fair
2013 Shenzhen Fair
2015 Shenzhen Fair