Parameter

SMQT

Pangalan ng Produkto	Outdoor waterproof Beam sensor
Model number	ABT
operating boltahe	13.8 ~ 24VDC 11 ~ 28VAC
operating kasalukuyang	40-65mA
Indikasyon speed	50 ~ 700m / sec
Anti-demolition output	NC
Environment temperatura	-20 ℃ ~ + 50 ℃
Alarm output	NO / NC
adjustment Level	180 ° ± 90 °
Vertocal adjustment	± 10 °
kulay	itim
materyal	PC dagta

Introduction

SMQT

PRODUCT PICTURE

Ang infrared beam barrier motion detector ay ginagamit sa bakod tulad ng

infrared bakod detector trabaho sa sistema ng alarma.

•Dimension

SMQT



•Feature

SMQT

PRODUCT FEATURE

Sealed integration structure is able to work inthe has enviroment

Automtically regulate to confranted with fog or inclement weathe

Sensitivity(AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built -in integrate optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes,low-power digital

•*Packaging & shipping*

SMQT

• *Office show*

SMQT

• *Exhibition*

SMQT

2011 Brazil Fair
2012 Shenyang Fair
2013 Jinan Fair
2013 Shenzhen Fair
共赢
.....
2012 Shenyang Fair
2013 Shenyang Fair
2013 Shenzhen Fair
2015 Shenzhen Fair