

• Parameter

SMQT

detalye	
Pangalan ng Produkto	2 beams outdoor infrared perimeter detector
modelo	ABT-20 ABT-40 ABT-60 ABT-80 ABT-100
distansya	20m 40m 60m 80m 100m (Panlabas) 60m 120m 180m 240m 300m (sa looban)
operating boltahe	13.8-24vDC 11-18vAC
operating kasalukuyang	40-65mA
induction speed	50-700m / sc
enviroment temp	-20 ° C-50 ° C
Alarm output	NO / NC
Anti-demolition output	NC
adjustment Level	180 ° (\pm 90 °)
vertical adjustment	\pm 10 °
materyal	PC dagta

• Introduction

SMQT



•Feature

SMQT



Sealed integration structure is able to work in the harsh environment
Automatically regulate to confront with fog or inclement weather
Sensitivity(AGC circuit)
easily adjust and calibrate the horizontal/vertical optional angle
Built-in integrated optical telescopes, anti-jamming jacket
Anti-lighting circuit designed
High-power infrared receiver on the tubes, low-power digital

• *Installation*

SMQT



•*Packaging & shipping*

SMQT

listahan packaging	
Pangalan ng Produkto	ABT 2 beams outdoor infrared perimeter detector
Dami	20 mga PC ng bawat karton
carton laki	51 * 48 * 38 (cm)
timbang	21kg



•Office show

SMQT



•Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

