

## ● Parameter

SMQT

Mga Dimensyon	85L * 52w * 25H (mm)
Standard Structure	Hindi masusunog materyales mixed dagta
electrical Performance	Kasalukuyang 3A @ 36VDC maximum na tibay
Makipag-ugnay sa output	NO / NC / COM
tibay test	500,000 beses aging nasubok
para sa Uri	Nauukol guwang frame at lubog electrical box
temperatura	-10 ~ + 55 °C (14-131F)
Nauukol halumigmig	0 Mga sa 95% (kamag-anak kahalumigmigan)
panel Processing	Hindi masusunog materyal naked ibabaw paggamot

## ● Introduction

SMQT

1. Ultra-mababang-kapangyarihan disenyo, lighting circuits ay maaaring konektado sa serye, unipolar control.
  2. Para sa lubog guwang frame at electrical box.
  3. Hindi masusunog materyales mixed dagta.
  4. daang libong beses nasubukan.
- Ang exit button switch ay infrared button at pinto release button. The button ginagamit sa sistema ng access control.

## ● Dimesion Picture

SMQT







● Packing list

SMQT



Dami	100 piraso / box
Packing Mismong	46.5L * 37.5W * 28H (cm)
Packing timbang	11.72Kg

● Office

SMQT



● Exhibitions



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....