

Specification	
Product Name	LED Backlight Door Release Button
Model	EA-27
Dimensions	86L * 86W * 20H (mm)
Supply voltage	Maximum current 3A @ 36VDC 12VDC durable
Standard Structure	Stainless steel panels, metal LIGHT
Contact output	NO / NC / COM contacts
Durability test	500,000 times aging tested
Panel Processing	Brushed stainless steel panel injection process
Temperature	-10 °C ~ + 50 °C
Applicable humidity	0-95% (relative humidity)
For Type	Applicable hollow frames
product weight	0.09Kg
Qty	100 / box

● Introduction

Illuminated stainless steel exit button, LED indicator light design, suitable for any access to go places for the opening, especially for dark places.

Stainless steel panels, brushed injection processing, high-end appearance of the atmosphere, refining process.

The price is cheaper, no computer knowledge decorators can be installed.

Suitable submerged hollow frames and electrical boxes to use.

● Dimesion Picture



Switch Power supply



Door release  
button EA-27



Converter  
(RS232 to RS485)



Standalone  
controller



PC



### THE ONE *Strong stability*

PC rubber seal lock core,  
resistance to heat shock,  
500, 000 times mechanical test  
qualified, suitable for all  
Access control system



### THE SECOND *Superior Design*

Simple and beautiful appearance,  
stainless steel wire drawing  
panel.

#### ● Packing list

**SMQT**

Packaging List	
Product name	LED Backlight Door Release Button
Qty	100 / box
Packing Specifications	46.5L * 37.5W * 28H (cm)
Packing weight	10.1Kg





## ● In the Office

SMQT



## ● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair