



Single door standalone controller keypad

Imported PC material shell 100000 user capacity

- ▶ IC card(13.56Mhz)
- ▶ IP66 grade waterproof
- ▶ Free software, RS485 communication format
- ▶ Can connect external WG(26/34) card reader

• Parameter

SMQT

number ng produkto	EA-92 (black and white opsyonal)
operating Boltahe	DC12 ± DC3V
Konsumo sa enerhiya	& Lt; 1W
Uri ng Card	125KHz ID
Pagbabasa distance	60mm
saklaw ng komunikasyon	150m
paraan ng komunikasyon	WG26 / 34
transmission rate	1bit / ms
Mga Dimensyon	96L * 96W * 22H (mm)
pabahay Material	PC
operating temperatura	-30 °C ~ + 65 °C

• Introduction

SMQT



2 Color optional
OLED Screen
Door bell button
Wear-resisting number key
Imported PC material shell

Ang rfid kalapitan card reader na may 125kHz at 13.56MHz frequency. This ay ang rfid tag reader magamit sa pinto access control system.

Mga natatanging disenyo (patent hitsura), ang shell ay nagyelo, kumportable.

Takeout doorbell button, panlabas na doorbell.

Communication WG26 / 34, maaaring ma-convert sa pamamagitan ng software.

Mataas na kaligtasan pagganap, hindi tinatagusan ng tubig (IP66), reverse kasalukuyang proteksyon, pakialaman, kidlat proteksyon.

Sa linya na may European / Asian pabalik laki ng kahon ng pag-install disenyo, madaling mga kable.

• *Installation*

SMQT



• Packaging & shipping

SMQT



• Office show

SMQT®



• Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

