Parameter SMQT

Dimensions	86L * 86W * 50H (mm)
Output port	NC / COM / NO
Application	Security doors, escape door
Optional accessories	Glass, transparent plastic surface cover
Working Temperature	-10 °C ~ + 50 °C
Materials	Fireproof ABS
Color	White,green,red,yellow

Introduction
SMOT

When the alarm occurs, break glass to alarm

Switching status: normally open / normally closed

Color: Red / yellow / white / green optional

Standard Structure: fireproof material shell, easy installation Application types: security doors, escape door, security system

Optional accessories: glass, transparent surface cover Processing panel: fireproof material, matte die-casting

Dimesion Picture SMQT





Installations
SMQT



■ Features SMQT

Manual fire alarm button, the structure is simple, modern design, easy installation. Be applicable In factories, warehouses,

hotels, and various large-scale use of the building fire alarm equipment. When the fire broke out , Press the start part,

Button to output an alarm signal immediately start the fire alarm and other linkage Fire Equipment. After the operation, no need

to replace parts started, simply reset with a key, you can re-use.





Glass

Packing list SMQT

Qty	100pcs/ CTN
Carton size	47L * 39W * 30H (cm)
Gross weight	17.44Kg



• Office SMQT













• Exhibitions SMQT

